

Budget PP tape Acryl high tack no noise



Product description:

No noise adhesive tape with solvent-free water-based acrylic adhesive. Characterized by the high tack formula. Suitable for medium weight box sealing with manual dispensers or automatic carton sealing machines. Resistant to UV rays and natural ageing.

FEATURES



No noise unwinding



High Tack formula



Solvent free



UV resistant

MAIN APPLICATIONS



Medium weight box sealing



Manual dispensers



Automatic carton sealing machines

BROWN

BACKING MATERIAL

BIAXIALLY ORIENTED
POLYPROPYLENE

TYPE OF ADHESIVE

WATER BASED ACRYLIC

COLOURS



BROWN



WHITE



TRANSPARENT

TECHNICAL DATA	Metric	Values	Test method
Backing thickness	µm	28	AFERA 5006
Total thickness	µm	52	AFERA 5006
Adhesion to steel	N/cm	2.6	AFERA 5001
Tensile strength	N/cm	45	AFERA 5004
Elongation at break	%	160	AFERA 5004

Technical Information, Storage, and Product Use

The product must be used within 12 months from the delivery date (6 months if jumbo). It is advisable to keep the material in its original packaging, away from heat sources and direct light. The storage temperature must be between 15°C and 30°C, with relative humidity between 40% and 60%. For storage temperatures outside these ranges, recondition the product to the levels described above.

The technical data shown in the data sheets represent the average of analyses obtained during normal production. Aging may cause variations in some technical and aesthetic characteristics of the product within the time limits indicated above without affecting its quality and functionality. The technical data provided have a tolerance of +/- 10% and may be modified at any time for production needs or technical updates.

Stipar declines all responsibility for direct damage and consequences resulting from improper use of the product.

It is advisable to verify the product's conformity in relation to specific usage conditions.